

# Wild Bill's Raceway

## Truck Rules 2010

### 1. TRUCKS

1. Full size only. No El Camino, Ranchero, Sonoma, etc.
2. Minimum weight 3,400 lbs.
3. Frame may be shortened to 101 inch wheelbase.

### 2 INSIDE DRIVER'S COMPARTMENT

1. Remove all flammable material. May leave front seat and dash or you may install a race type seat, properly mounted.
2. Race seat recommended. Aluminum seat should be used. All joints must be completely welded.
3. Must have at least six-point roll cage with door bars (driver side). 3 minimum.
4. All roll cagers must be 100% welded at all joints or you DO NOT RACE!!!! 1.75 outside diameter x .095 walls.
5. Must have a working (race approved) window net, no mesh or screen over driver window. Net must be secured to roll cage.
6. All holes in the fire wall and wall between the trunk and the driver must be plugged or covered. You may have two ½ inch holes in rear floorboard for drainage.

### 3. ENGINES

1. Casat Iron Blocks and intake may have aluminum intake. May have 6.5 inch plenum to carburetor mounting surface.
2. No decking. Must be in stock location.
3. Any flat top pistons. Engine must be stock with OEM Components only.
4. No head milling, and production head allowed. No pinning or screw in studs; only for repair of broken stud.
5. Any vacuum secondary carburetor, demons allowed. May use any two-barrel.
6. Cam up to .555 lift only hydraulic lifters. No roller lifters or rockers.
7. Distributors: any are allowed. Drive line 2" steel minimum.
8. Transmission: any type allowed. Stock disc 10-12 inches. No electric fans.
9. May change rear gears.
10. May Change rear ends.
11. Engines may be sealed at any time. If seals are tampered with, full penalties will be assessed.

#### **4. FUEL TANK**

1. Stock gas tank must be removed.
2. You can use a five or six gallon marine fuel tank. Must be securely mounted with straps or bands.
3. Fuel cell recommended.

#### **5. BATTERY**

1. Dry cell type securely mounted. Wet batteries must be in a sturdy box or container must be securely mounted.
2. Must have a battery disconnect switch and be within reach of the driver. Switch must be able to shut the truck off when all other switches are on.

#### **6. EXTERIOR BODY**

1. Remove all exterior trim and moldings.
2. Remove all glass. This includes no rearview mirror.
3. Hoods and trunks must be chained, bolted, pinned, welded, and must remain on the race. Minimum of two pins in front.
4. Bumpers must be strapped to fenders. You may remove fender wells.
5. Bumpers: No I-beams, No nerf bars outside of the body.
6. You may cut wheel wells for tires rub.
7. No alternating rooflines

#### **7. WHEELS AND TIRES**

1. Nothing wider the 8". No bead locks.
2. Up to a 275 DOT 60 series, any legal IMCA tire, American Racer, Hoosier
3. Must have 9/16 wheel studs on right side minimum.

#### **8. NO CLAIMER RULE!!!**

**BE A GOOD SPORT AND HAVE LOTS OF FUN!!**

**Wild Bill's Raceway has the right to eliminate and/or change these rules at anytime.**